

---

# Super POSS

---

Release 5.30

## Total Saving Installation instructions for NCR 2127 systems



10/24/2000  
Version 1.1



---

# Super POSS 5.30

---



## Total Savings Installation Instructions for NCR 2127 systems

### **Before you begin...**

- ➔ YOU MUST contact MEI Support personnel before beginning installation. Please call (800) 447-8849 between 5 a.m. and 4 p.m., Pacific Standard Time, Monday through Thursday.
- Make sure your system meets all requirements for the current version of Super POSS.

### **Installing the Total Savings Module**

- 1) Insert the first Super POSS diskette into the PC's disk drive.
- 2) At the DOS prompt, type:  

```
A: <Enter>  
\MEISETUP <Enter>
```

Where A is the letter of the drive into which you inserted the diskette. If your floppy drive is not A, try B.  
*The system displays this message:*  
**Can you display color?**
- 3) If yours is a color monitor, press <Enter> to accept the default (**Yes**). If not, tab to **No** and press <Enter>.  
*The system displays this message:*  
**This is the installation for:**  
  
**Super POSS Total Savings  
Version 5.30 2127 Sold System**
- 4) Press <Enter> to continue.  
*The system displays this message:*

**Enter the directory where you would like to install this product:**

**C:\Progra~1\Superp~1**

- 5) Press <Enter> to accept the default directory (C:\Progra~1\Superp~1).

*The system displays this message:*

**You have chosen to install the software in C:\Progra~1\Superp~1**

**Is this correct?**

- 6) Press <Enter> to accept the drive letter and directory as shown.

*The system displays this message:*

**Insert Disk # 1  
Installation Diskette**

- 7) Press <Enter> (OK)—Disk #1 should already be in your computer's floppy drive.

- 8) Continue inserting diskettes as prompted by the system.

*After the last diskette has been loaded, the system displays this message:*

**Installation Complete. You may now type exit to return to the desktop.**